Reflective FR Transfers

Domestic Wash

TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C):	150°C	
Temperature (°F):	300°F	
Time:	20-30 seconds	
Pressure:	Medium to	42.7 - 56.9 psi / 2.9 - 3.9 bar / 3.0 - 4.0 kg/cm2
	Low	28.4 - 42.7 psi / 2.0 - 2.9 bar / 2.0 - 3.0 kg/cm2
Carrier Release:	Warm/Cool peel	

LAUNDERING
Suitable for domestic wash up to 60°C
Tumble Dry - Medium
Iron - Medium, On Reverse
Do Not Dry-Clean
Do Not Bleach

HANDLING AND STORAGE
Store in a cool, dry place
Use within 12 Months
Keep away from direct sunlight
Do not attempt to apply any transfer that has been removed from its carrier
Direct contact with sweat or oils can cause stains/blemishes in the reflective surface. We recommend that gloves be worn when applying in order to preserve the finish of the product.

COMPOSITION
Micro glass-bead reflective film
Adhesive - TPU
Carrier - PSA

HEALTH & SAFETY
This product is identified as Non-Hazardous to the end user
No PPE is required during application**

ENVIRONMENTAL / RECYCLING
Vinyl - non-recyclable
Polyester carrier - non-recylable
Vegan-Friendly: No

CERTIFICATION
Reflective/wash Standards - EN ISO 20471:2013

**Any fumes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.